

# GMR

FORESTRY GRABS - GRAPPINS A BOIS - HOLZGREIFER - PINZAS CARGAS-TRONCOS



### Abbinamenti consigliati per escavatori

Suggested combinations for excavators - Coupages conseillées pour pelles  
Empfohlene Kupplungen für Bagger - Combinaciones recomendadas para las excavadoras

ton	A			B			C		
1,5 - 1,7	GMR 1000	C 10	PR 10	KIT 3/8"	CR 4/S	KAR 01/60	CR 8		
1,8 - 2,0	GMR 1050	C 35	PR 35	KIT 3/8"	CR 4/S	KAR 01/60	CR 8		
2,0 - 2,5	GMR 1050	C 35 F		KIT 3/8"	CR 4/S	KAR 01/60	CR 8		
2,5 - 3,5	GMR 1100	C 35 F		KIT 3/8"	CR 4	KAR 01/80	CR 8		
3,5 - 4,0	GMR 1300	C 35 F		KIT 3/8"	CR 4	KAR 01/80			
4,0 - 4,5	GMR 1300	C 50 FS		KIT 1/2"	CR 4	KAR 01/80			
4,5 - 6,0	GMR 1300 HD	C 50 FS		KIT 3/8"	CR 4	KAR 01/80			
6,0 - 6,5	GMR 1500	C 50 FS		KIT 1/2"	CR 4	KAR 01/80			
6,5 - 8,0	GMR 1500	C 65 F		KIT 1/2"					
6,0 - 8,0	GMR 1500 FX		CPR 9-01 PS 9-01	KIT 1/2"					
7,0 - 8,5	GMR 1750	C 65 F		KIT 1/2"					

**A** Attacco singolo perno  
One pin connection  
Attelage à axe simple  
Verbindung mittels Einfachbolzen  
Conexión de perno simple

**B** Kit per adattatore attacco rapido  
Kit for quick connection adaptor  
Kit pour adaptateur attelage rapide  
Kit für Schnellwechsler-Adapterplatte  
Kit para adaptador de conexión rápida

**C** Rotatore meccanico / Attacco escavatore  
Mechanical Rotator / Excavator attachment  
Rotateur mécanique / Croisillon pour pelle  
Mechanischer Rotator für Baggeranschluss  
Girador mecánico para conectar a la excavadora

## PINZE FORESTALI

ton 1,5 - 8,5

kg. 500 - 3000

		GMR 1000	GMR 1050	GMR 1100	GMR 1300	GMR 1300 HD	GMR 1500	GMR 1500 FX	GMR 1750
	ton	1,5 - 1,7	1,8 - 2,5	2,5 - 3,5	3,5 - 4,5	4,5 - 6,0	6,0 - 8,0	6,0 - 8,0	7,0 - 8,5
	Kg.	500	1000	1900	2100	2100	3000	2000	3000
	Kg.	48	63	85	118	141	196	232	265
	mm	1090	1120	1180	1400	1400	1610	1610	1740
	bar	100	200	200	200	200	200	200	200
	lt.	20	20	30	40	40	50	50	55
	m <sup>2</sup>	0,12	0,15	0,19	0,23	0,23	0,27	0,27	0,38
	mm	640	650	695	790	790	850	980	985
	mm	70	70	80	75	75	95	95	120
	mm	600	600	655	735	735	815	815	960
	mm	400	405	440	495	495	580	710	630
	mm	330	340	345	390	390	372	372	540
	mm	540	550	575	675	675	675	805	890
	mm	310	320	395	425	450	490	490	500

\* Resistenza strutturale a sollevamento - Résistance structurelle au levage - Structural strength to lifting - Strukturelle Festigkeit zu heben - Resistencia estructural a la elevación

	D	A	B
	CR 9		
	CR 9		
	CR 9		
	CR 9		
		CR 5	KAR 02
		CR 5	KAR 02

**D** Rotatore meccanico per adattatore attacco rapido  
Mechanical rotator for quick connection adaptor  
Rotateur mécanique pour adaptateur attelage rapide  
Mechanischer Rotator für Schnellwechsler Adapter  
Girador mecánico para adaptador de conexión rápida

kg.	A			B		
500	GMR 1000	C 10	PR 10	KIT 3/8"		
1000	GMR 1050	C 35	PR 35	KIT 3/8"		
1900	GMR 1100	C 35	PR 35	KIT 3/8"		
1900	GMR 1100	C 35 F		KIT 3/8"		
2100	GMR 1300	C 35	PR 35	KIT 3/8"		
2100	GMR 1300	C 35 F		KIT 3/8"		
2100	GMR 1300 HD	C 50	PR 50	KIT 3/8"		
2100	GMR 1300 HD	C 50 FS		KIT 3/8"		
3000	GMR 1500	C 50	PR 50	KIT 1/2"		
3000	GMR 1500	C 50 FS		KIT 1/2"		
3000	GMR 1500	C 65 F		KIT 1/2"		
3000	GMR 1750	C 65 F		KIT 1/2"		